

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>6</sup> : B01D 21/00, C02F 1/46, B01J 19/08</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/47230 (43) International Publication Date: 23 September 1999 (23.09.99)</p>
<p>(21) International Application Number: PCT/GB99/00755 (22) International Filing Date: 12 March 1999 (12.03.99) (30) Priority Data: 9805419.0 14 March 1998 (14.03.98) GB (71) Applicant (for all designated States except US): SPLITS TECHNOLOGIES LIMITED [GB/GB]; Elvingston Science Centre, By Galdismuir, East Lothian EH33 1EH (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): ZADIRAKA, Yuri Vladimirovich [UA/GB]; 8 Marchfield Park, Edinburgh EH4 5BW (GB). BARKHUDAROV, Eduard Mikhailovich [AM/RU]; Universitetskii Prospekt, 5, Fl. 24, Moscow, 117942 (RU). KOSSYL, Igor Antonovich [RU/RU]; Frunzenskaya Naberezhnaya, 26, Fl. 26, Moscow, 119164 (RU). TAKTAKISHVILI, Merab Ivanovich [GE/RU]; Building 2, Fl. 20, Donskaya, 21, Moscow, 117049 (RU). (74) Agents: MCCALLUM, William, Potter et al.; Cruikshank &amp; Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE (GB).</p>	<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report. Before the expiration of the time limits for amending the claims and to be republished in the event of the receipt of amendments.</p>	
<p>(54) Title: TREATMENT OF LIQUIDS</p>		
<p>(57) Abstract</p> <p>The present invention provides an apparatus suitable for use in the treatment of liquid (31), comprising a high voltage electric discharge device (8) with spaced apart first and second electrodes. The discharge device has electrical power supply control means (13) for applying a series of high voltage pulses across said first and second electrodes so as to produce an extended area electrical discharge in an electric discharge zone (37) extending between said first and second electrodes. The apparatus also has a gas delivery means (15-18) for feeding a series of bubbles of gas into the liquid in said electric discharge zone. The present invention also provides methods of producing an electrical discharge in a liquid and of decontaminating water and other liquids using the apparatus of the invention.</p>		

BEST AVAILABLE COPY

*FOR THE PURPOSES OF INFORMATION ONLY*

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

-1-

TREATMENT OF LIQUIDS

The present invention relates to the treatment of liquids, and more particularly to the treatment thereof so as to improve them through processing, e.g. inactivation or decomposition, of materials dissolved or suspended therein.

Electrical discharge is widely known in gases with various practical applications e.g. for lighting, cutting through metals etc. It is also known in principle that such an electrical discharge can be obtained inside a liquid. To date though this has not found any significant practical application due to inter alia the very short working life of the electrodes in the devices used.

It is an object of the present invention to avoid or reduce one or more of the above disadvantages.

The present invention provides an apparatus suitable for use in the treatment of a liquid, said apparatus comprising a high voltage electric discharge device with a first electrode and a second electrode spaced apart from said first electrode, said discharge device including electrical power supply control means formed and arranged for applying a series of high voltage pulses across said first and second electrodes in use of the apparatus with said device connected to an electrical power supply so as to produce, in use of the apparatus, an extended area electrical discharge in an electric discharge zone extending between first and second electrodes, said apparatus including a gas delivery means formed and arranged for feeding a series of bubbles of gas into a body of liquid in said electric discharge zone in use of said apparatus.

Thus with an apparatus of the present invention it is possible to generate an electrical discharge inside a liquid for treatment of the liquid, with a relatively low voltage

-2-

electrical power supply and in a way which results in substantially increased working life of the discharge device, with associated economy of construction, etc. Without in any way wishing to restrict the scope of the present invention, it is believed that a significant factor in the reduced voltage threshold required to establish the electrical discharge within the liquid in use of apparatus of the present invention is the generation of electrical discharge within the bubbles of gas passing between the electrodes.

10

The generation of a pulsed electrical discharge inside a liquid can induce various different and more or less powerful effects in the liquid depending on the form and type of apparatus of the invention used, which can have a strong effect on various materials present in the liquid. In general, within the immediate vicinity of the plasma discharge there are generated various more or less active species such as hydrated electrons, ions, excited atoms, and free radicals, which can react with materials present in the liquid. Zones of liquid extending beyond the immediate vicinity of the plasma discharge can be affected by UV-radiation. In the case of water containing trace amounts of material such as may be encountered in water being treated for domestic consumption, such zones may extend up to 6cms or more. The extent of such zones will naturally depend on various factors such as the intensity of the plasma discharge which in turn may depend to a greater or lesser extent on such factors as the voltage of the pulses used for the electrical discharge; and on the OD (optical density or absorbance of the liquid and any material dissolved or suspended in it). Acoustic and shock waves may also be generated by the plasma discharge. By using suitable geometric arrangements of secondary electrodes e.g. generally toroidal, it is possible to combine and concentrate such shock waves for even greater cumulative effect. It will moreover be appreciated that unlike with conventional UV-irradiation

-3-

apparatus, various embodiments of the apparatus of the present invention will have significantly more powerful effect from the UV-irradiation alone due to the avoidance of any barriers to UV-transmission between the source and the liquid being  
5 treated. Even quartz glass which has above average UV-transmission characteristics, substantially attenuates UV-radiation with a wavelength of less than 200nm. In addition, in at least some forms, the present invention can provide more or less significant synergistic effects through the  
10 combination of the UV-radiation, acoustic/shock waves generated, and plasma-chemical and photo-chemical reactions. This may be particularly significant in the treatment of liquids containing micro-organisms such as bacteria, so as to kill or inactivate these in order effectively to sterilise the  
15 liquid. The apparatus of the present invention may also be used to treat particular resistant infectious agents such as protozoal oocysts and prions.

Various liquids may be treated by use of the present  
~~20 invention, but the apparatus of the present invention is~~  
especially useful for the treatment of water contaminated with various different kinds of materials in order to improve the quality of the water, reduce environmental pollution etc. Thus the present invention may be used by public utility  
25 companies for the treatment of water supplied for consumption and running pools, and other uses, and for the treatment of waste water. Other liquids that may be mentioned as suitable for treatment include oils, for example used or waste transformer oil containing more or less toxic additives (e.g.  
30 PCBs - polychlorinated biphenyls) required for improving its performance, which require to be neutralised to facilitate safe disposal of the oil. Thus the present invention may also be used to decompose hazardous or toxic organo-chemicals into more or less safe and/or easily bio-degradable substances.  
35 Other organochemicals which may be mentioned as suitable for

-4-

neutralisation to a greater or lesser extent by means of the present invention include alkanols e.g. methanol; aldehydes e.g. formaldehyde; phenol and substituted phenols e.g. para-chlorophenol; etc. Other applications of the present invention which may be mentioned include activation of oils and generation of ultrasound for medical purposes.

It will be appreciated that various configurations and geometries of electric discharge device and of the electrodes used therein may be used in accordance with the present invention. In a first preferred form of the invention, the first and second electrodes are substantially spaced apart and there is provided a multiplicity of spaced apart secondary electrodes distributed between opposed portions of said first and second electrodes. Conveniently there is used a device form which has a generally annular electric discharge zone, which may be defined by an internal or external cylindrical surface, and having a longitudinal axis which may be substantially rectilinear, or arcuate to a greater or lesser extent e.g. circular (corresponding to a toroidal discharge surface) or helical, and extending between generally annular opposed portions of the first and second electrodes. With such non-rectilinear axis electric discharge zones it will be appreciated that there may be obtained a degree of interaction between shock or acoustic waves generated by the electric discharge, for example, to produce a more focused and intense cumulative effect.

Advantageously in the above described first form of the invention, the first electrode also has an elongate portion extending generally parallel to the electric discharge surface and insulated therefrom by a suitable solid insulator dielectric. Thus, for example, with an external electric discharge surface, said first electrode elongate portion could be in the form of a conductor extending generally along the

-5-

central longitudinal axis of the electric discharge surface. Conveniently the electric discharge surface is provided on the outside of a tubular insulator with an internal passage extending therealong inside which extends said conductor.

5

Without in any way wishing to restrict the scope of the present invention, it is believed that the operating principle of the above-described first form of electric discharge device of the present invention and its main advantage are based on  
10 the sequential breakdown of a series of interelectrode gaps and quick generation of an extended multi-spark surface discharge. At the initial point as the capacitance of the interelectrode gap is much less than the capacitance between the electrode and central conductor (said first electrode  
15 elongate portion), almost all voltage is applied to the first interelectrode gap (between the first and second electrodes). The sequence of successive breakdowns between the neighbouring electrodes results in the electric discharge being propagated from the first electrode portion to the second electrode via  
20 ~~the secondary electrodes along the metal-dielectric surface~~  
until the gap between the first electrode portion and the second electrode portion is fully bridged by a high-voltage pulse discharge of the kind sometimes referred to as "slipping surface" discharge. Thus the threshold of electric discharge  
25 initiation is decreased significantly and is close to the threshold of discharge between the two neighbouring electrodes e.g. the first electrode portion and the first one of the secondary electrodes. The use of the first electrode elongate portion has the particular advantage of substantially  
30 reducing, typically by 10 to 100 times, the threshold voltage required to initiate the electric spark discharge in a given device relative to that required in the same device without such a first electrode elongate portion extending alongside the electric discharge surface.

35

-6-

By dimensioning the internal passage in the abovedescribed type of arrangement of the first form of the invention, to have a diameter somewhat greater than that of the conductor, the passage can also serve as a conduit for gas as part of the gas delivery means. In this case the conduit may be connected to the discharge surface by a plurality of passage means extending through the insulator, which may be in the form of discrete space apart passages. Alternatively there could be used an insulator with a porous or honeycombed structure providing a large multiplicity of gas passages extending therethrough and which may be interconnected with each other to a greater or lesser extent.

In a second preferred form of the invention, the first and second electrodes are in the form of generally planar members in opposed relation, each having a plurality of apertures therein for the passage of liquid through first one and then the other of said electrodes via said electric discharge zone extending therebetween.

20

This second form of the invention is particularly suitable for use in continuous flow treatment of liquids for example, in public utility water supply systems. In this type of application, the first and second electrodes are mounted so as to extend substantially across the whole of the liquid is treated. The apertures in the first and second electrodes are generally formed and arranged in order to avoid creating excessive flow resistance whilst also providing a relatively substantial electrode structure resistant to erosion and low electrical resistance within the electrode structure itself. Desirably the electrodes are of a substantially uniform, e.g. honeycomb-like, structure across their transverse extent, with optionally an outer annular support or reinforcing portion.

Where required, e.g. in order to provide multiple discharge



-7-

treatments of a given body of water passing through the flow passage, and/or in order to ensure that all parts of the flow stream (along its longitudinal extent) are subjected to an effective discharge treatment - especially in the case of high flow rates, a plurality of opposed first and second electrodes may be used. This may be effected by the use of a series of devices mounted along the flow passage, or, more conveniently, by using a series of first and second electrode pairings connected (in parallel or series) to a common voltage supply means. In such cases the first and second electrode pairings may conveniently be spaced apart from each other by from 2 to 10cms, advantageously from 3 to 8cms, for example about 6cms. The first and second electrodes in the or each pairing are generally spaced apart from each other by from 0.2 to 2cms, preferably from 0.5 to 1cms.

As noted above, the electrodes may have various different forms corresponding to different proportions of electrode area v. aperture area. Typically the aperture area may comprise ~~from 30 to 98% of the total area of the electrode~~ (corresponding to an electrode material area of from 70 to 2% of the total area). Desirably the aperture area comprises from 50 to 95%, for example, from 70 to 90%, of the total electrode area.

25

In a third preferred form of the invention, the first electrode is provided at a nozzle means formed and arranged for directing, in use of the apparatus, a stream of said liquid onto said second electrode, said gas supply means being formed and arranged for injecting, in use of the apparatus, said series of bubbles of gas into said stream.

With this third form of device the amount of liquid within which the electrical discharge is generated and which is treated directly, is generally rather more restricted as

-8-

compared with the first and second forms of device. It is however also possible to use the more or less intense UV radiation generated by the plasma discharge within the stream of liquid, for irradiation treatment of other matter in proximity to said liquid stream. Thus, for example, a flow of liquid spaced apart from said liquid stream, may be treated.

With this third form of device, it will be appreciated that the electric discharge zone will have a somewhat different geometric configuration from that of the first and second types, and will be generally rod-shaped rather than tubular or sheet-form. Nevertheless, the form and arrangement of the electrodes as well as that of the electric discharge zone, may be varied considerably in this case also. In a simple arrangement the nozzle means is disposed substantially vertically above the second electrode so that a stream of liquid may simply fall under the influence of gravity down onto the second electrode. It is, however, also possible to use other arrangements in which a pressurized flow of liquid can be used to provide a jet of liquid onto a second electrode disposed other than vertically below a nozzle outlet, for example, to one side. The former type of arrangement is however generally preferred as it allows the use of a simple arrangement, e.g. a cup form recess, for collecting the liquid stream as it contacts the second electrode. Conveniently the nozzle itself is of an electrically conducting material in order that it can be used for or as the first electrode, though other arrangements are also possible e.g. with the first electrode as a partial or complete coating or nozzle tip attachment on a non-conducting nozzle. In the case of the second electrode this may also conveniently be integrated to a greater or lesser extent with a liquid stream collecting means, which generally has an enlarged diameter, and/or generally funnel-shaped, e.g. cup-shaped, inlet - especially where it is desired to use an essentially closed circuit

-9-

liquid supply for the liquid stream with the liquid stream being collected and returned, via suitable return passage means and flow inducing means e.g. a pump, to the nozzle. It will of course be appreciated that the return passage means should include electrical insulation means (or conveniently be of electrically insulating material) in order to electrically isolate the electrodes from each other along said passage means.

10 It will be appreciated that the size and form of the electric discharge zone in this third form of the invention may be varied. Thus the diameter of the nozzle outlet, as well as to some extent the liquid pressure and/or flow rate up to and through the nozzle, will affect the form and diameter of the stream of liquid. In general it is preferred to avoid high pressures and to have a relatively non-turbulent liquid flow (other than turbulence associated with the gas bubbles). Conveniently the liquid stream has a diameter of from 1 to 10mm, desirably from 2 to 7mm, though substantially larger

---

20 diameters may also be used if desired. The separation between the first and second electrodes may conveniently be in the range from 1 to 15cms, advantageously from 2 to 10cms. It will be appreciated in this connection that larger separations will generally require higher voltages.

25

In this third form of apparatus the gas supply is generally formed and arranged so that the injected gas is substantially entrained in the liquid flow passing out of the nozzle, as a series of relatively small gas bubbles.

30

In general the gas delivery means comprises passage means having outlet means at or adjacent said electric discharge zone, for feeding gas to the liquid in the electric discharge zone, and inlet means for coupling, in use of the apparatus, to a gas supply means which may comprise an active device such

-10-

as a compressor or pump, and/or a passive device such as a reservoir of compressed gas provided with a gas flow regulator means.

5 In general the gas delivery and supply means may be formed and arranged to feed gas to the liquid in said electric discharge zone at a wide variety of pressures and/or flow rates depending on various factors such as the gas used, the nature of the liquid, the size, shape and configuration of the  
10 electric discharge surface, the ambient pressure at the electric discharge surface, the high voltage pulse frequency etc. In the case of the first device form with multiple secondary electrodes, there may be used a gas feeding rate of at least  $30 \text{ l hr}^{-1}$ , conveniently from  $30$  to  $100 \text{ l hr}^{-1}$  for an  
15 electric discharge surface having an area of around  $25 \text{ cm}^2$ .

The gas supply means also desirably has outlet means formed and arranged to produce relatively small bubbles in the liquid, in use of the apparatus, with, for example, a bubble  
20 diameter in the range from  $0.1$  to  $10 \text{ mm}$ , preferably from  $0.5$  to  $5 \text{ mm}$ , advantageously from  $0.7$  to  $3 \text{ mm}$ .

Various gases may be used including more or less inert gases such as noble gases e.g. argon or nitrogen. Most  
25 conveniently and economically though there may simply be used air or oxygen which also have the advantage that they give rise to the production of ozone which can in turn allow the production of free radicals which can have further beneficial effects in the inactivation of contaminants.

30

The first and second electrodes may have various shapes and configurations depending inter alia on the shape and configuration of the electric discharge surface. Where this is generally annular, then the opposed portions of the first  
35 and second electrodes at respective end portions of the

-11-

electric discharge surface may also conveniently be annular but this is not essential. With an annular electric discharge surface the secondary electrodes are also conveniently generally annular. Other configurations are also possible though which may have possible advantages, for example, in relation to generation of a more homogenous electric discharge and/or increased electrode life. Thus, for example, the secondary electrodes may be in the form of multiplicity of metallic or other electrically conducting particles embedded in or attached to the surface of an electrically insulating substrate. The particles may have various shapes or sizes, for example, from 0.1 mm to 5 mm in diameter, conveniently from 0.2 mm to 0.3 mm in diameter, and may be rounded, but more conveniently are angular, for example polygonal, regular or irregular, star-shaped etc. The particles are generally spaced apart at a separation not less than their diameter, but conveniently of a similar order of magnitude. This type of arrangement has the advantage of generating a much larger number of electric spark discharge routes thereby yielding a

---

more homogeneous electric discharge zone.

In general it is desirable that there should be used an inter-electrode gap between neighbouring electrodes of at least 1 to 2 mm in order to ensure that an electric spark discharge occurs (i.e. substantially without electrical energy passage by other means). Larger gaps, for example up to 10 mm or more may be used without significantly increasing the threshold voltage - typically of the order of 10 kV, and are generally preferred as they provide a more extended electric spark discharge and zone. Preferably there is used an electrode gap of from 3 to 8mm. Larger gaps may also be used but these will tend to require higher threshold voltages.

The electrical power supply control means is generally formed and arranged for conditioning a suitable available electrical

-12-

power supply, in generally known manner, so as to apply across said first and second electrodes, a series of high voltage DC pulses. The voltage required to initiate and maintain an electric discharge may also be affected to some extent by various factors such as the shape and configuration of the electric discharge surface, the shape and configuration of the first and second electrodes and the secondary electrodes, as well as the number of the latter, and the liquid used. In addition we have found that by further increasing the applied voltage above the minimum threshold voltage required to initiate electrical discharge, it is possible to modify the spectral distribution of the UV radiation produced. More particularly we have found that higher voltages produce more higher energy shorter wavelength UV radiation i.e. the wavelength peak is shifted to shorter wavelengths e.g. from around 260nm which is particularly useful for inactivating bacteria and other micro-organisms, down to around 180nm which is more useful for removing formaldehyde and phenols. In addition at such shorter wavelengths there may be produced in water, new compounds such as  $H_2O_2$  and/or  $O_3$  which have oxidising properties and may provide further sterilisation of water and/or removal or inactivation of other undesirable contaminants. In general there is used a voltage of at least 10kV, usually from 10kV to 50kV.

25

The pulses may be applied at a range of different frequencies depending on, for example, the nature of the contaminant. Thus, for example, a higher pulsing rate may be desired where a shorter treatment time is required albeit at the cost of a higher power input requirement, or where the shock wave effect is considered particularly significant in the treatment. In general there is used a pulse rate which is sufficient to maintain a substantially continuous discharge. Conveniently there may be used a pulse rate of from 1 to 200Hz, e.g. from 1 to 100 Hz.

-13-

In a further aspect the present invention provides a method of producing an electric discharge in a liquid comprising the steps of: providing an apparatus of the invention coupled to  
5 an electrical power supply and a gas supply means; providing a body of said liquid between said first and second electrodes; and applying a series of high voltage pulses to the first and second electrodes of the electric discharge device of said apparatus while feeding gas into said body of liquid.

10

In a yet further aspect the present invention provides a method of producing an electric discharge in a liquid comprising the steps of: providing a first form of apparatus of the invention coupled to an electrical power supply and a  
15 gas supply means; substantially immersing the electric discharge surface of the electric discharge device in the liquid; and applying a series of high voltage pulses to the first and second electrodes of the electric discharge device of said apparatus while feeding gas to the electric discharge  
20 ~~surface thereof.~~

---

In yet another aspect the present invention provides a method of treating a liquid containing at least one hazardous contaminant, so as to decontaminate effectively the liquid  
25 said method producing and maintaining an electric discharge in said liquid by means of a method according to the present invention, for a period of time sufficient substantially to modify at least one said contaminant into a more benign form.

30 In accordance with the present invention the contaminant modification may have various different forms depending on the nature of the contaminant. In the case of micro-organisms the required modification should generally be at least sufficient to prevent effective propagation or reproduction of the micro-  
35 organism. In the case of cellular organisms such as bacteria,

-14-

suitable modification may or may not involve cell disruption. Various microbial contaminants may be inactivated by means of the present invention such as *E.coli*, *Pseudomonas aeruginosa*, *Cryptosporidium*, etc.

5

With organo-chemicals suitable modification comprises reaction of the contaminant so as to convert it into another species which is environmentally benign per se and/or which is more or less readily bio-degradable into an environmentally benign  
10 form. The method of the invention may also be used effectively to inactivate inorganic contaminants such as metal salts and especially heavy metal salts, by converting them into an insoluble form which can be more or less readily precipitated out of the liquid.

15

The decontamination method of the invention may be carried out in either a continuous treatment mode or a batch treatment mode. In the latter case the liquid to be decontaminated should generally be confined in a chamber around the electric

---

~~20 discharge device (or in a closed circuit including said~~  
chamber and liquid circulation means for circulating the liquid through the chamber) so that substantially the whole of the liquid is brought inside or into close proximity with the electric discharge zone for an effective period of time

25 sufficient for substantial inactivation of the contaminants.

The first preferred form of apparatus of the invention is generally most convenient for such treatment. The electric discharge itself will generally provide a more or less substantial degree of mixing of the liquid in the chamber but

30 if desired additional mixing means may be provided. In the case of a continuous treatment mode the apparatus of the invention would generally comprise a liquid containment means having an inlet for liquid to be treated, a treatment zone inside which the electric discharge surface of the electric  
35 discharge device is disposed, an outlet for treated liquid,



-15-

and liquid flow control means for regulating the flow of said liquid through the liquid containment means. The second preferred form of apparatus of the invention is generally most convenient for this.

5

The treatment time (discharge operation time for batch mode, or residence time in the electric discharge zone for continuous mode) will depend on various factors such as the nature of the liquid, and the nature and concentration of the  
10 contaminant(s), as well as the energy of the electric discharge. Suitable times can be readily determined by suitable trial and error for any given situation (device power and configuration, contaminant nature and loading thereof, required reduction in contaminant loading, etc.).

15

In order to increase efficiency in treatment of at least some contaminants of the liquid it may be desirable to control other variables as well. Thus for example in the treatment of water to inactivate micro-organisms it is preferred to use gas  
20 containing significant amounts of oxygen, and desirably to use alkaline pH values in the liquid undergoing treatment, typically from 7 to 11, preferably from 8 to 10, conveniently by means of adding alkali such as sodium hydroxide, in order to increase ozone generation and dissociation thereof to  
25 produce free radicals.

If desired, the treatments of the present invention may be combined to a greater or lesser extent with other possible treatments. Thus for example, the liquid being treated may  
30 also be heated in order to provide a more intensive and/or efficient treatment of the liquid. Also the liquid may be passed through a micro-filter.

In yet another aspect the present invention provided an  
35 apparatus suitable for use in the treatment of a liquid

-16-

comprising a high voltage electric discharge device with a first electrode and a second electrode spaced apart from said first electrode and a multiplicity of spaced apart secondary electrodes distributed between opposed portions of said first and second electrodes across an electric discharge zone of said device, said discharge device including electrical power supply control means formed and arranged for applying a series of high voltage pulses across said first and second electrodes in use of the apparatus with said device connected to an electrical power supply so as to produce an extended area electrical discharge, said apparatus including a gas delivery means formed and arranged for feeding gas to said electric discharge zone in use of said apparatus with said electric discharge zone immersed in said liquid.

15

Further preferred features and advantages of the invention will appear from the following detailed description given by way of example of some preferred embodiments and their use illustrated with reference to the accompanying drawings in

---

20 which:-

Fig. 1 is a schematic side elevation of a first type of water treatment system of the invention;

Fig. 2 is side elevation of a principal part of the electric discharge device of a first embodiment;

25 Fig. 3 is a detail side elevation of part of an electric discharge device of another embodiment;

Fig. 4 is partial schematic circuit diagram of the principal parts of the power control means of the apparatus of Fig.1.

Fig. 5 is a schematic side elevation of a second type of water treatment system of the invention; and

Fig. 6 is a schematic side elevation of a third type of water treatment system of the invention.

Fig. 1 shows a water treatment system of the first form of apparatus of the invention 1 comprising a liquid containment

-17-

vessel 2 in the form of an elongate chamber 3 having an inlet 4 at one end 5 and an outlet 6 at the other end 7. An electric discharge device 8 comprises an elongate body 9 mounting a series of electrodes 10 connected 11 to a high voltage power supply PS 12 via a power control means PC 13. The elongate body 9 has an internal passage 14 (see Fig. 2) and an air inlet 15 at one end 16 connected 17 to an air compressor C 18.

10 As shown in more detail in Fig. 2, the elongate body 9 comprises a hollow tube 19 of polytetrafluoroethylene, or other dielectric material with high voltage threshold breakdown (e.g. ceramic), with said air inlet 15 at said one end 16 and closed at its other end 20. An electric conductor 15 21 extends along the hollow interior 22 of the tube 19 and passes through said closed end 20 to be connected 23 to a first ring electrode portion 24 mounted on said closed end 20. A second ring electrode 25 is mounted on the open end 16 of the tube 19 and has connected 26 to it a return conductor 27.

---

~~20 A series of more or less closely spaced apart secondary ring electrodes 28 is mounted on the tube 19 between said first and second electrodes 24, 25. A series of small bores 29 extends through the wall 30 of the tube 19 from the central passage 14 and exiting between neighbouring electrodes 24, 28, 25. In more~~

25 detail the first electrode portion, the second electrode, and the secondary electrodes were each in the form of a titanium ring having a diameter of ca. 10mm, and axial length of 10mm, and a thickness of 2mm, with an interelectrode gap of 2mm therebetween.

30

In use of the apparatus liquid 31 is passed through the chamber 3 by means of a pump P 32 with a flow regulator R 33 for adjusting the liquid flow rate and air 34 is pumped into the tube 19 from which it escapes via the bores 29 as small 35 bubbles 36. Once the tube 19 has been filled with air, the

-18-

power supply 12 and power control means 13 may be activated to apply high voltage electric pulses to the first and second electrodes 24,25 to establish an electric discharge in an electric discharge zone 37 extending around the outer electric discharge surface 38 of the tube 19.

Fig. 3 shows another embodiment where the wall 39 of the tube 19 is porous defining a multiplicity of small passages 40 therethrough. On the outer surface 41 of the tube is embedded a large number of small particles of metal 42 constituting secondary electrodes which has the advantage of yielding a more homogeneous electric discharge over the electric discharge surface. In other respects the embodiment of Fig.3 may be substantially similar to the first described

embodiment. Fig. 4 shows the principal parts of the power control means 13 comprising a capacitor 43 in which charge is built up from the power supply means 12 prior to application to the electric discharge device 8 and discharge therethrough upon activation of a switch means 44. The circuit also includes suitable resistor means 45,46. Typically there are used particles 42 having a diameter of the order of 0.1 to 0.3mm which are spaced apart from each other - preferably by a distance not less than the particle diameter.

25

Fig. 5 shows schematically a preferred embodiment of the second form of the apparatus of the invention suitable for use in the treatment of a continuous flow 51 of water 52 through a pipeline 53. In more detail, the apparatus comprises a pair of disc form members 54, conveniently of stainless steel, mounted transversely across the interior 55 of the pipeline 53, approximately 1 cm apart and constituting the first and second electrodes 56, 57. The disc form electrodes 56, 57 are perforated with a multiplicity of more or less regularly spaced and closely spaced apart apertures 58 through which the water

-19-

flow 51 passes in use of the apparatus. The electrodes 56, 57 are connected to a high voltage pulse generator 59 similar to that described hereinabove, and a compressor 60 injects air 61 via a conduit 62 into the pipeline 53 so as to provide a stream of small bubbles 63 of air rising between the opposed first and second electrodes 56,57.

In use of the apparatus 50, when a high voltage pulse is applied an electric discharge spark 64 is initiated at a rising gas bubble and extends through the water between opposed portions of the first and second electrodes 56,57 creating an arc discharge in the water. After the spark 64 has died, the gas bubble continues to rise through the water 52. Since the gas in this bubble has become ionised, it is now easier to initiate an electric discharge spark at that bubble when the next high voltage pulse is applied. Thus a series of electric discharge sparks 64 is repeatedly induced at various positions across the pipeline thereby subjecting the water in the pipeline to the various powerful effects (intense UV radiation, acoustic/shock waves, free radicals etc. as discussed hereinbefore) thereby providing a particularly effective inactivating treatment of micro-organisms etc. present in the water 52. As the bubbles 63 are subjected to repeated electrical discharges they tend to dissolve in the water and thus not to accumulate inside the pipeline. Nevertheless, if desired, means may be provided for venting or otherwise removing any spent gas bubbles. In any event we have found that the apparatus performs satisfactorily even if a significant part of the pipeline cross-section is occupied by gas.

It will be appreciated that the main treatment effect is obtained in the general vicinity of the electric discharge zone 65 between the opposed first and second electrodes but can extend to a significant distance from the discharge zone

-20-

(possibly up to 200cm or more in clear drinking water) and that the water flows continuously through this electric discharge zone 65. Accordingly in order to ensure that all of the water flowing through the pipeline receives an effective treatment, especially in the case of high flow rates, it may be desirable to provide additional electrode pairs 66,67 (connected to the same high voltage pulse supply 59 or with independent supplies and/or to use a higher frequency pulse discharge. The spacing between neighbouring pairs may be selected relative to the water flow rate so that each and every portion of the water flow is subjected to a plasma discharge treatment time of a desired duration, which may moreover be effected in only one electric discharge zone 65 or inside multiple electric discharge zones. Thus it will be appreciated that it is in principle possible to achieve effective treatment with quite high flow rates.

It will also be understood that by varying the amount of gas injected it is possible to affect the number of discharge

---

20 pulses initiated between the electrodes in the case of smaller numbers of bubbles being injected, and minimisation of excess unused air being injected with higher numbers of bubbles being injected.

25 Fig. 6 is a schematic view of a preferred embodiment 70 of the third form of the apparatus of the invention suitable also for use in the treatment of liquids without the generation of plasma discharge and effects such as pressure shock waves inside those liquids. In more detail, this apparatus 70 has opposed first and second electrodes 71,72, in the form of a downwardly directed nozzle 73 and a funnel shaped collector 74 disposed below the nozzle 73. Water 75 is supplied to the nozzle 73 from a reservoir 76. A stream or jet 77 of water extends from the nozzle 73 to the receptacle 74 there it is collected and returned to the reservoir via a return pipe 78

-21-

provided with a pump 79. A compressor 80 pumps in air 81 immediately upstream of the nozzle 73 so as to inject a stream of gas bubbles into the water stream 77. As before the first and second electrodes 71, 71 are connected 85 to a high voltage pulse supply 86.

In use of the above described apparatus an electric plasma discharge is generated inside and along the length of the water stream 77 thereby treating the water inside the stream. 10 In addition though the intense UV radiation 87 emitted from the water stream 77 can be used to irradiate and treat a separate body of water 88 circulated inside a vessel 89 surrounding the water stream 77, with the aid of a pump 90.

15 With this embodiment the separation between the two electrodes - more particularly the tip 91 of the nozzle 73 and the funnel receptacle mouth 74, which typically is of the order of 10cms, can be readily adjusted by raising or lowering one or other (or both) of the electrodes 71, 73, for example, in order to  
~~20 increase the size of the discharge zone - using a higher~~  
voltage to initiate the discharge as required.

Various experiments were carried out using apparatus of the two principal types illustrated in Figs. 1 to 5 as described 25 hereinbelow. Two high voltage pulse supply devices having the following characteristics were used.

Type I - Peak voltage :  $U \approx 40\text{kV}$ ;

High-Voltage pulse duration :  $T \approx 150\text{ns}$ ;

Pulse energy :  $W \approx 0.1\text{ J}$ ;

30 Frequency of pulses repetition :  $f \approx 50\text{--}100\text{Hz}$

Type II - Peak voltage :  $U \approx 20\text{kV}$ ;

High-voltage pulse duration :  $T \approx 10\mu\text{s}$ ;

Pulse energy :  $W \approx 2\text{J}$ ;

-22-

Frequency of pulses repetition :  $f \approx 50\text{Hz}$ 

All chemical analyses and *Cryptosporidium* tests referred to in the following Examples were carried out by NAMAS accredited 5 laboratories.

Example 1 - Treatment of Contaminated Water

A vessel was filled with water (1000 ml) to which 10mg of parachlorophenol ( $\text{C}_6\text{H}_4\text{ClOH}$ ) was added as an admixture and the  
10 Electric Discharge device substantially as described above was placed in the vessel. The electric discharge device used was of cylindrical geometry containing 5 ring electrodes made of titanium with a diameter of ca. 10mm, a length of ca. 10mm and width of ca. 2mm. The 4 gaps between the electrodes had a  
15 clearance of ca. 2mm each. The dielectric tube supporting the electrodes was made of ceramics. Air at approximately atmospheric pressure was fed in through the holes in the interelectrode gaps at a rate of approximately 30 l/h: 10Hz, the period of irradiation -  $t = 8$  min. After the electric  
20 discharge treatment the content of parachlorophenol was found to have been decreased by 30%.

Example 2 - Treatment of Contaminated Water

Water (1l) containing *E.coli* ( $10^6$  organisms  $\text{l}^{-1}$ ) was placed in  
25 a container and an electric discharge device according to Figs.1 and 2 of the invention was immersed therein. An electric discharge was produced in the water and maintained for 10 minutes at a pulse rate of 10 Hz at a voltage of 20 kV.

30 Results

After treatment for 10 minutes the population of *E.coli* was decreased to undetectable levels.

Example 3 - Treatment of Water containing: (I) Bacteria/



-23-

(II) Protozoan oocystsI - Bacterial Inactivation

2.5 litres of water is treated in an apparatus similar to that of Figs. 1 to 4 and 5 litres in an apparatus similar to that of Fig. 5 with the water being continuously recycled through the pipeline. The water used was a 50x dilution of an activated sludge sample from an experimental waste water treatment plant. The amplitude of the high-voltage pulse was  $U = 40\text{kV}$ , the energy in the pulse was  $W = \text{ca. } 0.1 \text{ Joules}$ , and the pulse rate was  $f = 50 - 100\text{Hz}$  using a Type I voltage pulse supply.

The water was placed inside the tank and the first sample was taken immediately prior to switching on the voltage pulse supply. A total of five samples was taken each with a volume of approximately 30 ml. The samples were taken at 0, 10, 20, 30 and 40 min. Replicate analyses were carried out.

---

The samples were then processed to determine bacterial populations using the Miles-Misra plate counting technique and nutrient agar as the growth medium (Ref. 1). On each agar plate four drops of diluted sample of known volume (0.033) were placed using a pasteur pipette. The drops were then allowed to dry before incubation for 24 h at  $28^\circ\text{C}$  after 24 h, the plates were checked for growth and the number of colony-forming units (CFU)  $\text{ml}^{-1}$  of the original sample.

Results

Similar changes in bacterial populations were determined using both the first and second types of apparatus.

TIME	Bacterial Count (CFU*/ml)
0	63,000
10	2,000

-24-

20	0
30	0
40	0

\*CFU-Colony Forming Units

II - Cryptosporidium Inactivation

Oocysts from the protozoan *Cryptosporidium* are resistant to conventional treatments such as chlorination and are not destroyed unless very high (and dangerous) concentrations of chemical are used.

1.5 litres of water containing 2000 oocysts per millilitre were treated in an apparatus similar to that in Fig.5 with water being continuously recycled through the pipeline.

Samples from the recirculating water were analysed for viable oocysts at the start and after 30, 60, 90 and 120 min.

Results

Viable oocysts could not be determined at the 30 minute sample time and thereafter. Evidence of oocyst cell wall destruction and other degradation was found.

Example 4 - Degradation of Pentachlorophenol

To 5 l of water was added to PCP to provide an initial concentration of 48.24 µg/l. The solution was treated using an apparatus similar to that of Fig. 5 with 3 electrode pairs spaced 14 cm apart from each other, but with only one electrode pair active i.e. with high voltage pulses being supplied to it. Samples were collected at timed intervals during the treatment for chemical analysis and for toxicity testing using Microtox(Ref. 2).

Results

The following results were obtained.

Time (Min)	Pentachlorophenol (µg/l)	% Removed	Treatment efficiency per time period (%)
---------------	-----------------------------	-----------	------------------------------------------------

-25-

0	48.24	-	-
30	27.04	44.0	44.0
60	23.13	52.1	14.5
90	20.74	57.0	10.3
120	18.00	62.7	13.2

After treatment for one hour, 57.0% of the pentachlorophenol was degraded and 62.7% degradation occurred after two hours of treatment.

5

#### Example 5 - Degradation of 4-Chlorophenol

A similar procedure to that of Example 4 was carried out using water to which 4-CP had been added to provide an initial concentration of 376.11 µg/l.

10

#### Results

The following results were obtained.

Time (Min)	4-Chlorophenol (µg/l)	% Removed	Treatment efficiency per time period (%)
0	376.11	-	-
20	327.25	13.0	13.0
30	321.52	14.5	5.7
60	284.07	24.5	37.5
150	201.05	46.6	29.2

After treatment for one hour, 24.5% of the 4-CP was degraded and most degradation occurred after the first hour of treatment.

No toxicity was evident in the treated liquid containing 4-CP.

#### Example 6 - Degradation of Formaldehyde

20 A similar procedure to that of Example 4 was carried out using the effluent sample volume of 5 litres of water contaminated by formaldehyde ( 64 mg l<sup>-1</sup> ).

-26-

After treatment for two hours, 10% of the formaldehyde was found to have been degraded.

#### Example 7 - Degradation of Ammoniacal Nitrogen

5 The effluent sample volume of 5 litres of water contaminated by ammoniacal nitrogen ( 90 mg $l^{-1}$  ) which was then treated using a similar apparatus to that in example 4.

After treatment for two hours 50% of the ammoniacal nitrogen was found to have been degraded with most degradation

10 occurring during the first hour of treatment.

#### Example 8 - Degradation of Industrial Dyes

A sample of dark coloured industrial effluent containing dyes and heavy metals (Cd, Cr, Cu, Pb, Ni, Zn ) was diluted in

15 water 1 : 50 to provide 5 litres of contaminated water which was then treated using a similar apparatus to that in example 4. Samples of the treated water were recovered at timed intervals and assayed by means of visible light absorbance.

---

#### 20 Results

Absorbance measurement at different wavelengths between 400 and 700nm were made of the treated 1:50 dilution of the strongly coloured industrial effluent contained dyes and metals. It was found that treatment led to a decrease in

25 absorbance at all wavelengths tested indicating colour and metal reduction. An unusual finding was the initial increase in absorbance after 30 min treatment. This may have been due to production of fine metal particulates caused by the highly oxidised environment.

30

Time (Min)	Absorbance at Wavelength (nm)						
$\lambda$	700	650	600	550	500	450	400
0	2.47	2.87	3.28	3.65	3.87	4.15	4.38

-27-

30	2.87	3.35	3.83	4.28	4.56	4.87	5.13
60	2.67	3.12	3.57	4.00	4.25	4.53	4.81
120	2.56	2.99	3.42	3.84	4.08	4.35	4.59
180	2.30	2.69	3.09	3.46	3.67	3.91	4.13

Literature References

1. Miles, A. A. & Misra, S. S. (1938). The estimation of the  
5 bacterial power of the blood. Journal of Hygiene,  
Cambridge, 38, 732-749.
  2. AZUS Environmental (1997). Microtox Manual Volumes 1-4.  
Microbics Corporation. 2232 Rutherford Road Carlsbad, CA.
-

-28-

CLAIMS

1. An apparatus suitable for use in the treatment of a liquid,  
said apparatus comprising a high voltage electric discharge  
device with a first electrode and a second electrode spaced  
5 apart from said first electrode, said discharge device  
including electrical power supply control means formed and  
arranged for applying a series of high voltage pulses across  
said first and second electrodes in use of the apparatus  
with said device connected to an electrical power supply, so  
10 as to produce, in use of the apparatus, an extended area  
electrical discharge in an electric discharge zone extending  
between said first and second electrodes, said apparatus  
including a gas delivery means formed and arranged for  
feeding a series of bubbles of gas into a body of liquid in  
15 said electric discharge zone in use of said apparatus.
2. An apparatus according to claim 1 wherein said first and  
second electrodes are substantially spaced apart and there  
is provided a multiplicity of spaced apart secondary  

---

20 electrodes distributed between opposed portions of said  
first and second electrodes.
3. An apparatus according to claim 2 wherein said first and  
second electrodes are formed and arranged so as to provide  
25 an annular electric discharge zone in use of said apparatus.
4. An apparatus according to claim 3 wherein said electric  
discharge zone has a substantially rectilinear longitudinal  
axis.  
30
5. An apparatus according to claim 3 wherein said electric  
discharge zone has a longitudinal axis which is at least  
partly arcuate.
- 35 6. An apparatus according to claim 5 wherein said first and

-29-

second electrodes have opposed annular portions.

7. An apparatus according to claim 6 wherein the first electrode also has an elongate portion extending generally parallel to the electric discharge surface and insulated therefrom by a suitable solid insulator dielectric.
8. An apparatus according to claim 7 wherein said first electrode elongate portion is in the form of a conductor extending generally along the central longitudinal axis of the electric discharge zone.
9. An apparatus according to claim 8 wherein said electric discharge zone is provided on the outside of a tubular insulator with an internal passage extending therealong and providing a gas supply conduit, inside which passage extends said conductor.
10. An apparatus according to claim 9 wherein is provided a plurality of discrete spaced apart passage means extending through said tubular insulator for connecting said internal passage to the exterior of said tubular insulator for delivering gas to the electric discharge zone.
11. An apparatus according to any one of claims 3 to 10 wherein said secondary electrodes are generally annular.
12. An apparatus according to any one of claims 3 to 10 wherein said secondary electrodes are in the form of multiplicity of metallic or other electrically conducting particles embedded in or attached to the surface of an electrically insulating substrate.
13. An apparatus according to any one of claims 11 and 12 wherein the electrodes are spaced apart from each other by

-30-

from 3 to 8 mm.

14. An apparatus according to claim 1 wherein said first and second electrodes are substantially spaced apart with a  
5 multiplicity of spaced apart secondary electrodes distributed between opposed portions of said first and second electrodes so as to provide a slipping surface discharge across said electrodes in use of the apparatus.
- 10 15. An apparatus according to claim 1 wherein said first and said electrodes are in the form of generally planar members in opposed relation, each having a plurality of apertures therein for the passage of said liquid through first one and then the other of said electrodes via said electric  
15 discharge zone extending therebetween in use of said apparatus.
16. An apparatus according to claim 15 wherein is provided a multiplicity of said apertures distributed substantially  
20 uniformly across said electrodes.
17. An apparatus according to claim 16 wherein said apertures have an area comprising from 30 to 98 % of the total area of the electrodes.  
25
18. An apparatus according to any one of claims 15 to 17 wherein said apparatus comprises a plurality of first and second electrode pairs substantially spaced apart from each other.  
30
19. An apparatus according to claim 18 wherein each electrode pair is spaced from a neighbouring electrode pair by from 2 to 10 cms.
- 35 20. An apparatus according to any one of claims 15 to 19



-31-

wherein the or each first electrode is spaced from the opposed second electrode by from 0.2 to 2 cms.

21. An apparatus according to claim 1 wherein said first  
5 electrode is provided at a nozzle means formed and arranged for directing, in use of the apparatus, a stream of liquid onto said second electrode, said gas supply means being formed and arranged for injecting, in use of the apparatus, said series of bubbles of gas into said stream.
- 10 22. An apparatus according to claim 21 wherein said second electrode is provided in a generally funnel-form body formed and arranged for receiving and leading away liquid from said jet impinging thereon.
- 15 23. An apparatus according to claim 22 wherein is provided conduit means extending from said second funnel-form body to said nozzle and provided with pump means for circulating said liquid.
- 
- 20 24. An apparatus according to claim 23 wherein said nozzle means and said pump means are formed and arranged for providing a jet of liquid having a diameter of from 1 to 10 mm.
- 25 25. An apparatus according to any one of claims 21 to 24 wherein said first and second electrodes are spaced apart by from 1 to 15 cms.
- 30 26. An apparatus according to any one of claims 21 to 25 wherein said gas supply means is formed and arranged for injecting a stream of bubbles into said jet of liquid.
- 35 27. An apparatus according to any one of claims 21 to 26 which includes support means for supporting material to be

-32-

irradiated by said electric discharge in use of the apparatus, in proximity to and spaced apart from said liquid jet.

5 28. An apparatus according to any one of claims 1 to 27 wherein said electrical power supply control means is formed and arranged for applying said high voltage pulses at a voltage of from 10kV to 50kV.

10 29. An apparatus according to any one of claims 1 to 28 wherein said electrical power supply control means is formed and arranged for applying said high voltage pulses at a frequency of from 1 to 200 Hz.

15 30. An apparatus according to any one of claims 1 to 29 wherein said electrical power supply control means is formed and arranged for applying said high voltage pulses with a pulse energy of from 0.01 to 50 J per pulse.

---

20 31. An apparatus according to claim 30 wherein is used a pulse energy of from 0.1 to 25 J.

32. A method of producing an electric discharge in a liquid comprising the steps of: providing an according to claim 1  
25 coupled to an electrical power supply and a gas supply means; providing a body of said liquid between said first and second electrodes; and applying a series of high voltage pulses to the first and second electrodes of the electric discharge device of said apparatus while feeding gas into  
30 said body of liquid.

33. A method of producing an electric discharge in a liquid comprising the steps of: providing an according to claim 2  
coupled to an electrical power supply and a gas supply  
35 means; substantially immersing the electric discharge

-33-

surface of the electric discharge device in the liquid; and  
applying a series of high voltage pulses to the first and  
second electrodes of the electric discharge device of said  
apparatus while feeding gas to the electric discharge  
5 surface thereof.

34.A method of treating a liquid containing at least one  
undesirable form contaminant, so as to decontaminate  
effectively the liquid, said method comprising the steps of  
10 producing and maintaining an electric discharge in said  
liquid by means of a method according to claim 32 or claim  
33, for a period of time sufficient substantially to modify  
at least one said contaminant into a more benign form.

15 35.A method according to claim 34 wherein said liquid  
undergoing treatment has a pH of from 7 to 11 during said  
treatment.

36.A method according to claim 34 or claim 35 wherein is used  
20 a gas comprising oxygen.

---

37.A method of decontaminating water containing a microbial or  
other infectious agent contaminant, wherein said water is  
treated by a method according to any one of claims 34 to 36.  
25

38.A method of decontaminating water containing a heavy metal  
or other chemical contaminant, wherein said water is treated  
by a method according to any one of claims 34 to 36.

30 39.An UV radiation source comprising an apparatus according to  
any one of claims 21 to 26.

1/3




Fig. 1




Fig. 2




Fig. 3

SUBSTITUTE SHEET (RULE 26)

WEST

2/3




Fig. 4




Fig. 5

SUBSTITUTE SHEET (RULE 28)




Fig. 6

SUBSTITUTE SHEET (RULE 26)

# INTERNATIONAL SEARCH REPORT

Int. onal Application No  
PCT/GB 99/00755

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 B01D21/00 C02F1/46 B01J19/08

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B01D C02F B01F B01J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 23285 A (PHILIPS ELECTRONICS NV ;PHILIPS NORDEN AB (SE)) 3 July 1997  see page 6, line 32 - page 8, line 10; figures ---	1-4, 11, 13, 14, 28-39
X	US 5 630 915 A (GREENE HUGH W ET AL) 20 May 1997 see column 3, line 43 - column 4, line 30 see column 8, line 10-65 ---	1, 28-39
X	EP 0 431 190 A (MITSUBISHI ELECTRIC CORP) 12 June 1991 see column 1, line 3 - column 2, line 46 -----	1, 28-39

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"A" document member of the same patent family

Date of the actual completion of the international search

5 July 1999

Date of mailing of the international search report

12/07/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Persichini, C

# INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/GB 99/00755

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9723285 A	03-07-1997	EP 0873184 A US 5766447 A	28-10-1998 16-06-1998
US 5630915 A	20-05-1997	US 5464513 A BR 9506486 A CA 2178963 A CN 1138316 A EP 0739311 A JP 9507428 T CA 2126935 A WO 9518768 A	07-11-1995 07-10-1997 13-07-1995 18-12-1996 30-10-1996 29-07-1997 12-07-1995 13-07-1995
EP 0431190 A	12-06-1991	DE 69001351 T WO 9100247 A JP 2503763 B US 5139625 A	21-10-1993 10-01-1991 05-06-1996 18-08-1992



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**